

Specification

Model:		10423-35
Electrical Characteristics	Nominal voltage	12.8V
	Nominal capacity	200Ah
	Energy	2560Wh
	Cycle Life	>3000 cycle @80% DoD, discharge rate 0.5C, 25°C
	Months Self Discharge	≤3.5% per month at 25°C
Standard charge	Charge Voltage	14.6±0.2V calculated according 3.65V voltage of each cell
	Charge Mode (CC/CV)	At 0°C~45°C temperature, charged to 14.0V at a constant current of 0.2C, then charged continuously with constant voltage of 14.6V until the current no more than 0.02C
	Standard Charge Current	40A
	Max.Charge Current	100A
Standard discharge	Max.Continuous discharge Current	200A
	Peak discharge current	400A(<3S)
	Discharge Cut-off Voltage	10.0V
Temperature	Charge Temperature	0°C to 45°C(32°F to 113°F) @60±25% Relative Humidity
	Discharge Temperature	-20°C to 60°C(-4°F to 140°F) @60±25% Relative Humidity
	Storage temperature	-10°C ~ + 45°C
Bluetooth Function		/
Low Temperature protection		/
Terminal		M8
Battery Weight		Approx.17.65KG
Battery Dimension		345*190*245mm
Housing		ABS
Marking terminal		Positive pole "+", negative "-"
Parallel function		Support 4pcs in parallel
Series function		Support 4pcs in serial