

Model 24

360 Gallons Per Hour



	13.6v	12.0v
GPH @ Open Flow	360	330
GPH @ 3.35' feet in lift	265	240
GPH @ 6.7' feet in lift	190	150

FEATURES

- Fully Submersible
- Easy clean snap lock strainer
- Silent and vibrationless operation
- Anti-airlock protection
- Compact, efficient long life motor
- Ignition protected
- No burn-out when run dry
- Rust and Corrosion protection
- Used by leading boatbuilders worldwide
- marine grade blocked wiring

	13.6v	12.0v
Maximum Amp Draw	2.5	2.1

ANSWERS TO FREQUENTLY ASKED QUESTIONS

- Not Self Priming
- Discharge hose must run continually upwards
- Reductions in hose size will reduce output
- Increases in hose size will not increase output
- Reversed polarity runs pump at 20% capacity
- Increase wire gauge for each add'l 20 foot run
- Check valves are not recommended
- Install a vented loop for anti-siphoning
- Break in for 10 hours for maximum pumping
- Rule does not repair pumps - it is not cost efficient for the consumer
- Rule does not sell pump parts due to liability

CERTIFICATIONS

- NMMA Type Accepted Equipment # 704180
- IMCI Certified - ISO 8849
- CE Certified
- UPC Code 0-42237-08345-6

Specification	
Fuse Size	2.5 amps
Discharge Opening	3/4"
Discharge Finish	Barbed
Rule Hose	Model 81 or 82
Rule Thru-Hull Fitting	Model 61 or 61S
Housing Material	ABS
Strainer Material	ABS
Impeller Material	Nylon
Shaft Material	Stainless
Seal Material	Nitril/Teflon
Temperature Limit	200 F
Fluid Capabilities	Bilge Water
Typical Life	1500 hours
Wire Length	29"
Wire Gauge	16 gauge
Weight	9 oz
Height	3-1/2"
Width	2-3/8"
Depth	2-3/8"
Strainer Replacement	part M275