

ICOM

VHF MARINE TRANSCEIVER

IC-M73EURO

***Slim, Stylish, Powerful VHF
with Professional Features***



Last Call Voice Recording

The last call voice recording function automatically saves the last incoming call for 1 minute. You can also start recording manually. You will not miss an important call.



Active Noise Cancelling Technology

The built-in bidirectional active noise cancelling reduces background noise to up to 90% and improves both your transmitted voice and incoming call. You will hear better and clearer!



Bass Boost Function

The signal processing technology emphasizes low-pitched sound to provide a rich bass sound for both transmit and receive signals.



700mW Loud Audio



6W RF Output Power



IPX8 Advanced Waterproofing

700mW Loud Audio

The IC-M73EURO uses a BTL (bridge-tied load) amplifier that doubles the audio output. Its internal speaker delivers a loud 700mW audio output with clear sound.

6W RF Output Power

The IC-M73EURO's 6 Watts*1 of transmit power will provide extended communication range for the user. A large capacity Lithium-Ion battery, BP-245H allows for 17 hours of operation, under normal conditions*2.

*1 1W for FRG version, *2 Typical operation with 5:5:90 duty ratio. 20 hours for basic version.

IPX8 Advanced Waterproofing

The IC-M73EURO continues to offer Icom's best waterproof protection. The radio has been tested to survive after being submersed in 1.5m (4.9ft) depth of water for 30 minutes.

**Slim, Hourglass Body
Wide Viewing Angle LCD**

The IC-M73EURO has a stylish, ergonomic design. A durable and rugged body provides for user-friendly operation and long life. A wide viewing angle, high intensity LCD offers bright, easy to read characters.

Additional features

- AquaQuake™ water draining function
- Dual/Tri-Watch function* for monitoring Channel 16 and/or call channel
- 4 level battery indicator
- Favorite channel and tag scan functions
- Optional waterproof speaker-microphones, HM-167 and HM-202
- Rapid charger BC-210 supplied
- Auto power save function
- Basic version (no voice recorder, no noise canceller and no bass boost function) available for limited markets.

* Not available in the HOL version.

SPECIFICATIONS

GENERAL		
Frequency range	Tx	156.000–161.450MHz
	Rx	156.000–163.425MHz
Usable channel groups	INT, USA* channels (* Depending on version)	
Type of emission	16K0G3E (FM)	
Current drain		
Tx 6W output	1.5A	
Rx Max. audio (Int SP/Ext SP)	450mA/250mA	
Operating temp. range	–15°C to +55°C	
Antenna impedance	50Ω (SMA)	
Dimensions (W×H×D) (projections not included)	52.5×125×30 mm	
Weight (approx.)	320g (With BP-245H, FA-S64V, MB-103)	

Measurements made in accordance with EN301-178-2. All stated specifications are subject to change without notice or obligation.

TRANSMITTER	
Output power (Hi/Mid/Low)	6W/3W/1W 1/0.5W (FRG version)
Max. frequency deviation	±5.0kHz
Frequency stability	±1.5kHz
Spurious emissions	0.25μW
Adjacent channel power	70dB
Audio harmonic distortion	Less than 10% (at 60% dev.)
Residual modulation	40dB
RECEIVER	
Sensitivity (at 20dB SINAD)	–4dBμ emf typ.
Squelch sensitivity	–5dBμ emf typ. (at threshold)
Adjacent channel selectivity	70dB
Spurious response	70dB
Intermodulation	68dB
Hum and noise	40dB
Audio output power (at 10% distortion, 8Ω load)	700mW typ. (Internal SP@1kHz) 200mW (External SP)

Applicable U.S. Military Specifications & IP Rating

Standard	MIL 810G	
	Method	Procedure
Low Pressure	500.5	I, II
High Temperature	501.5	I, II
Low Temperature	502.5	I, II
Temperature Shock	503.5	I-C
Solar Radiation	505.5	I
Rain Blowing/Drip	506.5	I, III
Humidity	507.5	II
Salt Fog	509.5	–
Dust Blowing	510.5	I
Immersion	512.5	I
Vibration	514.6	I
Shock	516.6	I, IV

Also meets equivalent MIL-STD-810-C, -D, -E and -F.

Applicable IP Rating

Ingress Protection Standard	
Water	IPX8 (Waterproof protection)

OPTIONS

Some options may not be available in some countries. Please ask your dealer for details.

BATTERY PACK



BP-245H Li-Ion 7.2V,
2150mAh (min.), 2200mAh (typ.).

RAPID CHARGER



BC-123SE **BC-210**

Charges the BP-245H in 3 hours (approx.).

MULTI-CHARGER



BC-197 **BC-157S**

Charges up to six BP-245H in 3 hours (approx.).
AD-129 is supplied with the BC-197, depending on version.

Supplied Accessories:



- Cigarette lighter cable, CP-25H* • AC adapter, BC-123SE*
- Rapid charger, BC-210 • Battery pack, BP-245H
- Belt clip, MB-103 • Antenna, FA-S59V or FA-S64V*
- Hand strap

* Not supplied or may differ depending on version.

SPEAKER-MICROPHONES



HM-167 IPX8 rugged type
HM-202 IPX7 compact type

BELT CLIPS




MB-86 Swivel type
MB-103 Alligator type

LEATHER BELT HANGERS



MB-96N Swivel type
MB-96F Fixed type
MB-96FL Long type

CIGARETTE LIGHTER CABLE & DC POWER CABLES



CP-25H For use with BC-210
OPC-515L For use with BC-210
OPC-656 For use with BC-197

ANTENNAS



FA-S59V (Left) 150mm
FA-S64V (Right) 115mm

Icom, Icom Inc. and the Icom logo are registered trademarks of Icom Incorporated (Japan) in the United States, the United Kingdom, Germany, France, Spain, Russia and/or other countries. AQUAQUAKE is a trademark of Icom Inc. (Japan) in the United States. All other trademarks are the properties of their respective holders.

Icom Inc. 1-1-32, Kami-minami, Hirano-ku, Osaka 547-0003, Japan Phone: +81 (06) 6793 5302 Fax: +81 (06) 6793 0013

www.icom.co.jp/world

Count on us!

Icom America Inc.
12421 Willows Road NE,
Kirkland, WA 98034, U.S.A.
Phone: +1 (425) 454-8155
Fax: +1 (425) 454-1509
E-mail: sales@icomamerica.com
URL: <http://www.icomamerica.com>

Icom (Europe) GmbH
Communication Equipment
Auf der Krautweide 24
65812 Bad Soden am Taunus, Germany
Phone: +49 (6196) 76685-0
Fax: +49 (6196) 76685-50
E-mail: info@icom-europe.com
URL: <http://www.icom-europe.com>

Icom France s.a.s.
Zac de la Plaine,
1 Rue Brindejonc des Moulinais, BP 45804,
31505 Toulouse Cedex 5, France
Phone: +33 (5) 61 36 03 03
Fax: +33 (5) 61 36 03 00
E-mail: icom@icom-france.com
URL: <http://www.icom-france.com>

Asia Icom Inc.
6F No. 68, Sec. 1 Cheng-Teh Road,
Taipei, Taiwan, R.O.C.
Phone: +886 (02) 2559 1899
Fax: +886 (02) 2559 1874
E-mail: sales@asia-icom.com
URL: <http://www.asia-icom.com>

Your local distributor/dealer:

Icom Canada
Glenwood Centre #150-6165
Highway 17A, Delta, B.C.,
V4K 5B8, Canada
Phone: +1 (604) 952-4266
Fax: +1 (604) 952-0090
E-mail: info@icomcanada.com
URL: <http://www.icomcanada.com>

Icom Spain S.L.
Ctra. Rubi, No. 88 "Edificio Can Castanyer"
Bajos A 08174, Sant Cugat del Valles,
Barcelona, Spain
Phone: +34 (93) 590 26 70
Fax: +34 (93) 589 04 46
E-mail: info@icomspain.com
URL: <http://www.icomspain.com>

Icom (Australia) Pty. Ltd.
Unit 1 / 103 Garden Road,
Clayton, VIC 3168 Australia
Phone: +61 (03) 9549 7500
Fax: +61 (03) 9549 7505
E-mail: sales@icom.net.au
URL: <http://www.icom.net.au>

Icom Brazil
Rua Itororó, 444 Padre Eustáquio
Belo Horizonte MG,
CEP: 30720-450, Brazil
Phone: +55 (31) 3582 8847
Fax: +55 (31) 3582 8987
E-mail: sales@icombrasil.com

Icom (UK) Ltd.
Blacksole House, Altira Park,
Herne Bay, Kent, CT6 6GZ, U.K.
Phone: +44 (0) 1227 741741
Fax: +44 (0) 1227 741742
E-mail: info@icomuk.co.uk
URL: <http://www.icomuk.co.uk>

Icom New Zealand
39C Rennie Drive, Airport Oaks,
Auckland, New Zealand
Phone: +64 (09) 274 4062
Fax: +64 (09) 274 4708
E-mail: inquiries@icom.co.nz
URL: <http://www.icom.co.nz>