



ACCUSATO™

POCKET SERIES 406 MHz PLB

MT410 / MT410G 406 MHz EMERGENCY PERSONAL LOCATOR BEACONS

Fitted with
NON-HAZMAT
Long Life
Batteries

- GPS OPTION AVAILABLE (MT410G POCKET PRO+)
- 7 year Battery life, 7 year Warranty.
- Typical accuracy - MT410G: <100m MT410: <5km.
- High visibility flashing light.
- Unique patented technology - no warm up period.
- Featherweight, compact and robust construction.
- Digital 406 MHz, 5 Watt transmission plus 121.5 MHz homing signal.
- COSPAS-SARSAT worldwide operation.
- National & International Approvals.
- Sealed waterproof design (exceeds IP67).
- Retention strap and fully buoyant design reduces risk of loss.
- Complete with protective carry pouch.



www.gme.net.au



GME's AccuSat Series, available with or without an integrated GPS option, are leading the world with feature innovation and user benefits.

Not only is the AccuSat Series the smallest and lightest PLB on the market, both models offer a massive 7 year battery replacement life, an 'industry first' 7 year warranty, a high intensity flashing LED and a 'Non Hazmat' battery pack for simple and cost effective transportation, all contributing to the unique AccuSat advantage.

The current 121.5/243 MHz analogue COSPAS SARSAT service will be terminated in February 2009 and only the 406 MHz digital beacon signals will be processed thereafter. Consumers have for some time recognised the major benefits of a 406 MHz over a 121.5 MHz device in faster, more accurate detection, personal identification of each beacon, reduced search area resulting in a faster more targeted response in a life threatening situation. However the prohibitive cost of 406 MHz beacons has always been an issue.

Today with cutting edge microprocessor technology, GME's engineers are able to provide the outdoor adventurer with a 406 MHz PLB solution that is not only affordable, but provides enhanced peace of mind for boaters, bush walkers, 4 x 4 enthusiasts and aviators should they ever require emergency assistance.

GME has been designing and manufacturing emergency beacons in Australia for over 30 years. In that time literally hundreds of lives have been saved in Australia and around the world.

For information on the MT410/G or any GME product please visit our website:

www.gme.net.au

MODES OF OPERATION

- Activated:** UHF (406) and VHF (homer) complete with high intensity strobe and audible alert.
- Self Test:** Comprehensive internal diagnostics with visual and audible operator feed-back. UHF test message (inverted synchronisation compatible with portable beacon testers). GPS satellite acquisition test (MT410G only)

OPERATION

- Activation:** Automatically when antenna deployed
- Duration:** In excess of 24 hours at -20 °C Longer at higher ambient temperatures.
- Transmission:** 121.5 MHz and 406 MHz
- Delay:** 60 seconds to de-activate prior to distress transmission.
- Warm Up:** None required (due to patented digital frequency generation)
- VHF:** 121.5 MHz, 50 mW ±3 dB, swept tone AM (analogue)
- UHF:** 406.028 MHz, 5 W ± 2 dB, PSK (digital)
- LED:** > 20 flashes/minute
2 x high intensity white LED
- COSPAS-SARSAT:** Certified to C/S T.001 (Class 2) requirements
- Approvals:** AS/NZS 4280.2
ETSI EN 302 152-1
- UHF-Protocol/Data:** Supports all short (MT410) and long (MT410G) operation protocols (reprogrammable by Distributor)
- Repetition Period:** 50 s mean, digitally generated randomization
- VHF:** Satellite compatible phase coherent

BATTERY

- Replacement Period:** Prior to expiry date marked on case - (7 yrs)
- Replacement Method:** Service centre or factory only (non-user replaceable)
- Battery Chemistry:** LiMnSO₂ (0.49 g Lithium per cell)
- Battery Configuration:** 2 electronically isolated batteries, each consisting of 2 cell types CR17345

PHYSICAL

- Operating:** -20 to +55 °C
- Storage:** -30 to +70 °C
- Weight:** MT410 - 235 g
MT410G - 250 g
- Compass Safe Distance:** 0.1 m (for minimal deflection)
- Dimensions (mm):** 135 (h) x 71 (w) x 38 (d)
- Buoyant:** Will float in fresh/salt water (RTCM Cat2)
- Waterproof:** Submersion to 1 m
- Materials:** High visibility yellow chassis with translucent cap. UV stabilised high impact plastic chassis with energy absorption overmoulded bumpers.

GPS RECEIVER (FITTED TO MT410G ONLY)

- Type:** Ultra-high sensitivity L1 frequency C/A
- Channels:** 16 Channel, 8192 time/frequency search windows
- Antenna:** Dielectrically loaded quadrifilar helix
- Acquisition:** Cold start 34 seconds typical
Hot start <3.5 seconds typical
- Position:** Located to within 100 m typical

OTHER FEATURES

- Transport:** Meets UN requirements for transport as Non-hazardous cargo on board passenger aircraft
- Antenna:** Flexible and robust wire rope design. Marine grade 316 stainless steel.
- Included Accessories:** Wrist/Neck strap. Protective carry pouch with multidirectional belt loops.
- Antenna:** Flexible self straightening stainless steel design



Specifications are subject to change without notice or obligation.

Dealer: _____

A Division of **Standard Communications PTY. LTD.**

HEAD OFFICE: Locked Bag 2086 NORTH RYDE N.S.W. 1670 Australia.
 Phone: +61 (0)2 9844 6666 Fax: +61 (0)2 9844 6600 Email: export@gme.net.au
 MELBOURNE: (03) 9798 0988 BRISBANE: (07) 3278 6444 PERTH: (08) 9455 5744
 SYDNEY: (02) 9879 8888 ADELAIDE: (08) 8234 2633 AUCKLAND: (09) 274 0955

