



.... Sanimarin 31

THANKS TO ITS COMPACT FOOTPRINT THIS MODEL FITS EASILY INTO CONFINED SPACES.



TECHNICAL FEATURES

Pumping height	3 m
Horizontal pumping distance	30 m
Non return valve	Integrated
Outlet diameter	38 mm or 25 mm
Supply voltage	12 V or 24 V DC
Motor power	300 W (12 V), 360 W (24 V)
Electricity consumption	Dependent upon the control system (see detail p.30)
Water consumption	Dependent upon the control system from 1.2 L to 2.4 L
Water use	- Onboard freshwater (integrated solenoid valve) or outside pressurised water - Minimum pressure of supplied water 1.7 bar - Recommended pump flow rate 11 L/min
Weight	17 kg

REFERENCES

DESIGNATION	CODE	EAN
Sanimarin 31 Comfort 12 V	SN3112VLC	3308815012148
Sanimarin 31 Comfort 24 V	SN3124VLC	3308815012162
Sanimarin 31 Plus 12 V	SN3112VLC	3308815012155
Sanimarin 31 Plus 24 V	SN3124VLC	3308815012179
Sanimarin 31 Premium 12 V	SN3112VPREMIUM	3308815077864
Sanimarin 31 Premium 24 V	SN3124VPREMIUM	3308815077871
Sanimarin 31 Luxe SFA 12 V	SN3112VCLAVSFA	3308813412018
Sanimarin 31 Luxe SFA 24 V	SN3124VCLAVSFA	3308813424011

4 CONTROL SYSTEMS



Electric switch **Comfort**




Pneumatic button **Plus**



Electric button **Premium**



Electronic keyboard **Luxe**



Mounting on a raised step



Small dimensions



Connection to the pressurised water onboard



Easy to use



Quiet



Soft close seat

TECHNICAL VIEWS



DIMENSIONS (MM)

