



.... Sanimarin 43

WITH ITS PURE AND SIMPLE LINES, IT FITS EASILY INTO ALL SPACES.



..... COMFORTABLE AND FUNCTIONAL

TECHNICAL FEATURES

Pumping height	3 m
Horizontal pumping distance	30 m
Non return valve	Integrated
Outlet diameter	38 mm or 25 mm
Supply voltage	12 V or 24 V DC
Motor power	300 W (12 V), 360 W (24 V)
Electricity consumption	Dependent upon the control system (see detail p.30)
Water consumption	Dependent upon the control system from 1.2 L to 2.4 L
Water use	- Onboard freshwater (integrated solenoid valve) or outside pressurised water - Minimum pressure of supplied water 1.7 bar - Recommended pump flow rate 11 L/min
Weight	23 kg

REFERENCES

DESIGNATION	CODE	EAN
Sanimarin 43 Comfort 12 V	SN4312VLC	3308815077918
Sanimarin 43 Comfort 24 V	SN4324VLC	3308815077925
Sanimarin 43 Plus 12 V	SN4312VLCPLUS	3308815077932
Sanimarin 43 Plus 24 V	SN4324VLCPLUS	3308815077949
Sanimarin 43 Premium 12 V	SN4312VPREMIUM	3308815077956
Sanimarin 43 Premium 24 V	SN4324VPREMIUM	3308815077963
Sanimarin 43 Luxe 12 V	SN4312VCLAVSFA	3308815077970
Sanimarin 43 Luxe 24 V	SN4324VCLAVSFA	3308815077987

4 CONTROL SYSTEMS



Electric switch **Comfort**



Pneumatic button **Plus**



Electric button **Premium**



Electronic keyboard **Luxe**



Vertical back line



Installation distance from black water tank



Connection to the pressurised water onboard



Quiet Acoustic pressure : 52 dB(A)



Easy to use



Soft close seat

TECHNICAL VIEW



DIMENSIONS (MM)

